M500

IN-CAR VIDEO SYSTEM

In your vehicle out in the field, your eyes are your first line of defense. You're trained to constantly scan your surroundings for threats — to yourself and to the public. It's intense, highly demanding work. But with our technology, you can lighten that load and heighten your situational awareness like never before.

The M500 in-car video system is a groundbreaking leap forward in awareness, safety and efficiency. It's not just an eye recording what it sees, it's a brain analysing everything around you. Powerful video analytics — driven by industry-leading 4k video — constantly process your surroundings, alerting you in real time to threats and search targets

And the M500 seamlessly coordinates with the mission critical technology you already count on — from body-worn cameras, to evidence management platforms.

When you're only as safe as what you can see, the M500 gives you real time awareness of what's happening around you. It's a watchtower calling out what you need to know. A partner that takes you to a new level of calm and collected. Because the more you know what's out there, the more you can keep yourself and the people you serve safe.





MOTOROLA

SCAN. ANALYSE. BEACT.

FEATURES



M500 CORE PROCESSOR



M5F FRONT CAMERA



M5P CABIN CAMERA



M5R REAR CAMERA



M5D CONTROL PANEL

M500 KEY FEATURES

Front Camera Recording	Support for high resolution front camera
Cabin Camera Recording	Support for daylight and infrared cabin camera with integrated microphone
Cabin Microphone Recording	Support for discreet cabin microphone x2
Rear Camera Recording	Support for high resolution rear camera
USB Drive Support	Support for configuration and firmware updates via removable USB drive
USB Evidence Backup	Removable USB Drive can be used for storing and offloading video evidence*
Auto-record Triggers	System can be triggered to record by vehicle speed, lights, siren, aux input x2
Auto-stop Record	Configurable maximum length of video recordings
GPS Support	Support for GPS location information and timing reference
WiFi Event Upload	System can upload events to DEMS solution via Wi-Fi access point
LTE/WiFi Router Upload	System can upload events via a Sierra Wireless LTE/Wi-Fi modem/router
Encryption	Video evidence is encrypted at rest and in transit
Officer Settings	User access to system preferences to adjust display brightness, etc
Event Playback	Video and audio can be played back on the control panel / display
Record-after-the-Fact™	Events can be recovered from the system even if no recording was initiated

System firmware can be upgraded over a wireless link
System can record 2 streams and select upload resolution based on event tagging
System can be configured to record with no visual or audio indicators
System can be configured to turn off screen, and button backlights
System can log key parameters for debug purposes
System can recognise vehicle impact and automatically start recording
System can self-power for several seconds in case of vehicle collision / power failure
System can read number plates and interface with Vigilant LEARN database
Cabin camera will automatically record when a human is detected in back seat*
System will capture panoramic and detailed views (at 2 resolutions each)
Synchronised Playback Support for Synchronised playback in Management platform
Live-streaming Video and audio streaming to Management platform*

PAGE 2

DATA SHEET | M500 IN-CAR SYSTEM

^{*}Feature not supported at launch





MOO

M500 CORE PROCESSOR KEY FEATURES

Form Factor	Single DIN
Dimensions (H x W x D)	180 x 49 x 171 mm
Weight	1.4 kg
Operating Temperature	-30°C to +65°C
Mounting Option	Overhead (vehicle-specific brackets) or universal mount
Recording Media (Internal)	1 TB automotive-grade solid state drive
Recording Media (Removable)	128 GB USB Drive*
GPS	Integrated
Crash Detection	6-axis sensor
Additional Input / Outputs	USB, Ethernet, wired microphone (x2), trigger interface (2 AUX inputs), wireless microphone (x2), powered ethernet (x4)*
Video Transfer Methods	Wireless 802.11 router, optional WiFi or all-in-one LTE/Wi-Fi Router, Ethernet, USB*
Max Camera Capacity	Up to 5 cameras (Initial release: 2)
Resolutions	1920x1080p, 1280x720p, 864x480p (dual stream, configurable), with configurable high/medium/low bitrate
Frame Rate	30, 15, 10, & 5 fps (configurable)
Multiple Resolution Encoding	Records two resolutions simultaneously (patented): 1080p/720p, 1080p/4080p, or 720p/480p

Recording Triggers	Lights, siren, AUX triggers (x2), impact/ crash, speed, wireless microphone, backseat occupancy
Storage	Dual drive architecture*
Pre-Event	None, 15 sec, 30 sec, 45 sec, 90 sec, 1 min, 2 min, 3 min, 5 min, or 10 min
Redundancy	Record-After-The-Fact (patented, configurable)
Recording Capacity	Dependent on recording resolution, frame rate and cameras connected: Video 1080p@30fps High Quality = 4.5GB per hour per stream 720p@30fps High Quality = 2.25GB per hour per stream 480p@30fps High Quality = 1GB per hour per stream Audio 23.4MB per hour per stream
Wi-Fi	Wi-Fi, LTE/Wi-Fi routers
Security	FIPS-140-2 compliant encryption
Cabin Camera Audio	Integrated MEMs microphone (digital audio over coax)

*Feature not supported at launch



FRONT CAMERA





Discoursians (II o M o D) including baselest	40 40 00
Dimensions (H x W x D), including bracket	43 x 40 x 69 mm
Weight	85.4 g
Operating Temperature	-30°C to +65°C
Connection	Bayonet-locking HDBNC for power and data
Aspect Ratio	Electronic panoramic view (simultaneous wide and cropped streams)
Horizontal Field of View	Wide panoramic stream: 102/119° with/without dewarp Cropped stream: 51/59.5° with/without dewarp
Low Light Performance	Below 0.1 lux
Sensor Resolution	3840x1920 pixels
Sensor Technology	8MP, BL-CMOS (backlit CMOS)
Sensor Area	2.5 x 4.3 mm
Mounting	Windshield puck or ball mount









CONTRACTION OF THE PARTY OF THE

M5P CABIN CAMERA KEY FEATURES

Dimensions (H x W x D)	113 x 48 x 39 mm
Weight	150 g
Operating Temperature	-30°C to +65°C
Connection	Single HD-BNC connection for power and data
Resolution	1920x1080
Viewing Angle	108° (horizontal)
Low Light Performance	0 lux (infrared illumination)
Infrared Illumination	940nm, not visible
Audio	Integrated MEMs microphone (digital audio over coax)
Environmental Protection	IP54, MIL-STD 810G
Mounting	Tamperproof screws or zip ties, 180-degree rotation







MER





M5R REAR CAMERA KEY FEATURES

Dimensions (H x W x D)	70 x 65 x 41 mm
Weight	135 g
Operating Temperature	-30°C to +75°C
Connection	Single HD-BNC connection for power and data
Resolution	1920x1080 at 30 fps
Viewing Angle	108o (wide view)
Low Light Performance	0.07 lux
Sensor Technology	CMOS
Mounting	Variable adjustment mount (ball and socket)
Environmental Protection	IP54







MOTORIOLA © MOTORIOLA MS5000

M5D CONTROL PANEL KEY FEATURES

Dimensions (H x W x D)	110 x 144 x 36 mm
Weight	30g
Operating Temperature	-30°C to +65°C
Connection	Single HD-BNC connection for power and data
Screen Size	5" diagonal
Screen Resolution	1920x1080
Screen Brightness	600 nits
Touchscreen Technology	Capacitive multi-touch
Dedicated Controls	Power, home, record, stop, cameras, display
Mounting	B-size RAM mount
Other	Silicone overmold for secure grip



M500

NOW OBSERVATION BECOMES ACTION

SUPPORT

WARRANTY

Comprehensive 12-month product warranty included.

Warranty may be optionally extended to 5 years at additional cost.

For more information, please visit www.motorolasolutions.com/M500

Motorola Solutions LIK Ltd. Nova South, 160 Victoria Street, London, SW1E 5LB, United Kingdor

Availability is subject to individual country law and regulations. All specifications shown are typical unless otherwise stated and are subject to chang without notice.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2022 Motorola Solutions, Inc. All rights reserved. (10/22)



