Issue date: 31-January-2022

Revision date: -

Supersedes date: 27-Dec-2016

Version number: 02



SAFETY DATA SHEET

1. Identification

Product identifier Nickel Metal Hydride (NiMH) Batteries

Other means of identification None.

Recommended use of the chemical and restrictions on use

Recommended use Nickel metal hydride battery.

Restrictions on use Not available.

Details of manufacturer or importer

Company name Motorola Solutions Australia Pty Ltd

Address 10 Wesley Court

East Burwood VIC 3151

Australia

General information +61 3 9847 7500

Emergency phone number

CHEMTREC (Australia): +61 2 9037 2994 **CHEMTREC (International):** +1-703-741-5500

Customer number 204471

2. Hazard(s) identification

Classification of the hazardous chemical

Physical hazards Not classified.

Health hazards Not classified.

Environmental hazards Not classified.

Under normal conditions of processing and use, exposure to the chemical constituents in this product is unlikely. The battery should not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful.

Label elements, including precautionary statements

Hazard symbol(s) None.
Signal word None.

Hazard statement(s) The mixture does not meet the criteria for classification.

Precautionary statement(s)

Prevention Handle with care. For safe handling, see Section 7.

Response See Sections 4, 6 and 8 for response information.

Storage Store as indicated in Section 7.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Other hazards which do not result in classification

In the event of damage resulting in a leak of exposed materials, avoid contact with contents of an

ttion open or damaged cell or battery.

Supplemental information None.

3. Composition/information on ingredients

Mixture

Identity of chemical ingredients	CAS number and other unique identifiers	Concentration of ingredients %
Positive electrode (Nickel metal, Nickel hydroxide)	7440-02-0, 12054-48-7	10-25
Positive electrode (Cobalt)	7440-48-4	<10
Negative electrode (Metal hydride alloy may contain: Lanthanum, Cerium, Neodymium, Praseodymium)	7439-91-0, 7440-45-1, 7440-00-8, 7440-10-0	5-15

Nickel Metal Hydride (NiMH) Batteries

Version #: 02 Revision date: - Issue date: 31-January-2022

SDS Australia

Negative electrode (May contain: Nickel)	7440-02-0	10-30
Negative electrode (May contain: Cobalt)	7440-48-4	<10
Electrolyte (May contain: Potassium Hydroxide, Sodium Hydroxide)	1310-58-3 1310-73-2	10-15
Other components (Nylon, Polypropylene, Steel)	-	10-28

Composition comments

All concentrations are in percent by weight unless otherwise indicated.

Exposure to hazardous ingredients is not anticipated under normal conditions of use.

4. First-aid measures

Description of necessary first aid measures

Inhalation Exposure to contents of an open or damaged battery: If breathing is difficult, remove to fresh air

and keep at rest in a position comfortable for breathing. Call a physician or poison control centre

Skin contact Exposure to contents of an open or damaged battery: Remove contaminated clothes and rinse

skin thoroughly with water for at least 15 minutes. Call a physician or poison control centre

immediately. Chemical burns must be treated by a physician.

Exposure to contents of an open or damaged battery: Immediately flush eyes with plenty of water Eye contact

for at least 15 minutes. Provide eyewash station. Remove contact lenses, if present and easy to

do. Continue rinsing. Call a physician or poison control centre immediately.

Exposure to contents of an open or damaged battery: Call a physician or poison control centre Ingestion

immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that

stomach content doesn't get into the lungs.

Personal protection for first-aid

responders

Use personal protective equipment sufficient to prevent direct skin or eye contact or inhalation of this product. If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Symptoms caused by exposure

Exposure to contents of an open or damaged battery: Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause allergic skin reaction. Difficulty in breathing. Coughing. Prolonged exposure may cause chronic effects.

Medical attention and special

treatment

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media

Leak from a damaged or opened battery: Do not use water unless flooding amounts are available.

Specific hazards arising from the chemical

In the event of fire and/or explosion do not breathe fumes. Irritating, corrosive and/or toxic gases or fumes will be released during a fire. Combustion products may include: carbon oxides, metal

Special protective equipment

oxides. Wear full protective clothing, including helmet, self-contained positive pressure or pressure

and precautions for fire fighters

demand breathing apparatus, protective clothing and face mask.

Fire fighting

equipment/instructions

Fight fire from protected location or safe distance. Keep upwind. Move containers from fire area if you can do so without risk. Avoid discharge into drains, water courses or onto the ground.

Hazchem Code None.

General fire hazards Under normal use, the battery does not exhibit flammable properties. Exposure to excessive heat

may lead to venting or rupture of the sealed battery, exposing the internal components which may

be corrosive and toxic.

Use standard firefighting procedures and consider the hazards of other involved materials. Specific methods

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

None under normal use conditions. In the event of damage resulting in a leak or exposed materials, avoid contact with contents of an open or damaged cell or battery. Wear protective clothing as described in section 8 of this safety data sheet.

Nickel Metal Hydride (NiMH) Batteries Revision date: -Issue date: 31-January-2022 2/8 For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

Environmental precautions Avoid allowing material from exposed battery to contaminate soil, sanitary sewers, or waterways.

Methods and materials for containment and cleaning up

Leak from a damaged or opened battery: Contain spillage with sand or earth. Transfer to a container for disposal. For waste disposal, see Section 13 of the SDS.

Other issues relating to spills and releases

Clean up in accordance with all applicable regulations.

7. Handling and storage

Precautions for safe handling

Do not open, disassemble, crush or burn battery. Protect against physical damage. Do not expose battery to extreme heat or fire. Do not allow conductive material to touch the battery terminals. A dangerous short-circuit may occur and cause battery failure and fire.

Conditions for safe storage, including any incompatibilities

Keep out of reach of children. Prevent short circuits. Store in original packaging. Store in a cool, dry, ventilated area away from sources of heat, moisture and incompatibilities. Store away from incompatible materials (See Section 10). Do not store at temperatures above 60 °C (140 °F).

8. Exposure controls and personal protection

Control parameters

Follow standard monitoring procedures.

Occupational exposure limits

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)

Components	Туре	Value	Form
Cobalt (CAS 7440-48-4)	TWA	0.05 mg/m3	Dust and fume.
Nickel (CAS 7440-02-0)	TWA	0.1 mg/m3	
Nickel hydroxide (CAS 12054-48-7)	TWA	0.1 mg/m3	
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3	
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	

Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)

Components	Туре	Value	Form
Cobalt (CAS 7440-48-4)	TWA	0.05 mg/m3	Dust and fume.
Nickel (CAS 7440-02-0)	TWA	1 mg/m3	
Nickel hydroxide (CAS 12054-48-7)	TWA	0.1 mg/m3	

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
Cobalt (CAS 7440-48-4)	TWA	0.02 mg/m3	
Nickel (CAS 7440-02-0)	TWA	1.5 mg/m3	Inhalable fraction.
Nickel hydroxide (CAS 12054-48-7)	TWA	0.2 mg/m3	Inhalable fraction.
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3	
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	

UK. EH40 Workplace Exposure Limits (WELs)

Components	Туре	Value	
Cobalt (CAS 7440-48-4)	TWA	0.1 mg/m3	
Nickel (CAS 7440-02-0)	TWA	0.5 mg/m3	
Potassium hydroxide (CAS 1310-58-3)	STEL	2 mg/m3	
Sodium hydroxide (CAS 1310-73-2)	STEL	2 mg/m3	

Argentina. Biological Exposure Indexes (BEIs) (Decree 351/1979)

Components	Value
Cobalt (CAS 7440-48-4)	15 μg/l
Exposure guidelines	Airborne exposures to hazardous substances are not expected when product is used for its intended purpose.
Appropriate engineering controls	General ventilation normally adequate. Leak from a damaged or opened battery: Provide adequate ventilation if fumes or vapours are generated.
Individual protection measures, for example personal protective equipment (PPE)	
Eye/face protection	None under normal conditions. Leak from a damaged or opened battery: Wear approved safety glasses or goggles.
Skin protection	
Hand protection	None under normal conditions. Leak from a damaged or opened battery: Wear protective gloves.
Other	None under normal conditions. Leak from a damaged or opened battery: Wear suitable protective clothing and gloves.
Respiratory protection	None under normal conditions. Leak from a damaged or opened battery: Wear suitable respiratory protection.
Thermal hazards	Not applicable.
Hygiene measures	Do not store food, drink and tobacco near the product. Practice good housekeeping.

Nickel Metal Hydride (NiMH) Batteries

SDS Australia Version #: 02 Revision date: - Issue date: 31-January-2022

9. Physical and chemical properties

Appearance

Physical state Solid. **Form** Battery. Colour Not available. Odour Not available. Not available. **Odour threshold** Not available. Ha Not available. Melting point/freezing point Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Will burn if involved in a fire.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Vapour pressureNot available.Vapour densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other physical and chemical parameters

Explosive properties Not explosive. **Oxidising properties** Not oxidising.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Product is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials. Elevated temperatures. Shocks and physical damage. Do not

open, disassemble, crush or burn battery. Do not allow conductive material to touch the battery

terminals. A dangerous short-circuit may occur and cause battery failure and fire.

Incompatible materialsDo not immerse in seawater or other high conductivity liquids.

Hazardous decomposition

products

Thermal decomposition or combustion may produce: carbon oxides, metal oxides

11. Toxicological information

Information on possible routes of exposure

Inhalation Not relevant, due to the form of the product. Exposure to contents of an open or damaged battery:

Prolonged inhalation may be harmful.

Skin contactNot relevant, due to the form of the product. Exposure to contents of an open or damaged battery:

Causes severe skin burns. May cause an allergic skin reaction.

Eye contact Not relevant, due to the form of the product. Exposure to contents of an open or damaged battery:

Causes serious eye damage.

Ingestion Not relevant, due to the form of the product. Exposure to contents of an open or damaged battery:

Causes digestive tract burns. Harmful if swallowed.

Nickel Metal Hydride (NiMH) Batteries

SDS Australia

Version #: 02 Revision date: - Issue date: 31-January-2022

Symptoms related to exposure

Exposure not expected under normal use conditions. In the event that cell or battery is damaged, open, or leaking - inhalation, skin contact, and/or eye contact may be considered for routes of exposure. Signs and symptoms may include: Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause allergic skin reaction. Difficulty in breathing. Coughing. Prolonged exposure may cause chronic effects.

Acute toxicity

Expected to be a low hazard for usual industrial or commercial handling by trained personnel. Exposure to contents of an open or damaged battery: May be harmful if swallowed or inhaled.

Components Species Test results

Nickel hydroxide (CAS 12054-48-7)

Acute Inhalation

LC50 Rat 1.2 mg/l, 4 Hours

Oral

LD50 Rat 1540 mg/kg

Potassium hydroxide (CAS 1310-58-3)

Acute Oral

LD50 Rat 273 mg/kg

Skin corrosion/irritation Exposure to contents of an open or damaged battery: Causes severe skin burns. **Serious eye damage/irritation** Exposure to contents of an open or damaged battery: Causes serious eye damage.

Respiratory or skin sensitisation

ACGIH sensitisation

HARD METALS CONTAINING COBALT AND Respiratory sensitisation

TUNGSTEN CARBIDE, THORACIC FRACTION, AS CO

(CAS 7440-48-4)

Respiratory sensitisation Exposure to contents of an open or damaged battery: May cause allergy or asthma symptoms or br

Skin sensitisation Exposure to contents of an open or damaged battery: May cause an allergic skin reaction. **Germ cell mutagenicity** Exposure to contents of an open or damaged battery: Contains a suspect mutagen.

Carcinogenicity Exposure to contents of an open or damaged battery: May cause cancer.

ACGIH Carcinogens

Cobalt (CAS 7440-48-4)

A2 Suspected human carcinogen.

A3 Confirmed animal carcinogen with unknown relevance to

humans.

Nickel (CAS 7440-02-0) A5 Not suspected as a human carcinogen.

Nickel hydroxide (CAS 12054-48-7)

A1 Confirmed human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cobalt (CAS 7440-48-4)

2B Possibly carcinogenic to humans.

Nickel (CAS 7440-02-0)

2B Possibly carcinogenic to humans.

Nickel Metal Hydride (NiMH) Batteries

Version #: 02 Revision date: - Issue date: 31-January-2022 6 / 8

Nickel hydroxide (CAS 12054-48-7) 1 Carcinogenic to humans.

Reproductive toxicity Exposure to contents of an open or damaged battery: May damage fertility or the unborn child.

Specific target organ toxicity -

single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity -

repeated exposure

Exposure to contents of an open or damaged battery: Causes damage to organs through

prolonged or repeated exposure:

Not relevant, due to the form of the product. **Aspiration hazard**

Chronic effects Exposure to contents of an open or damaged battery: Prolonged inhalation may be harmful.

Prolonged exposure may cause chronic effects.

Other information Exposure to hazardous ingredients is not anticipated under normal conditions of use.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test results**

Lanthanum (CAS 7439-91-0)

Aquatic Acute

EC50 Other Daphnia sp.

43 µg/l, 48 hours

Nickel (CAS 7440-02-0)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 1 mg/l, 48 hours

1 mg/l, 48 Hours

LC50 Calanoid copepod (Pseudodiaptomus

6.17 - 12.4 mg/l, 72 hours

coronatus)

Potassium hydroxide (CAS 1310-58-3)

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) 80 mg/l, 96 Hours

Sodium hydroxide (CAS 1310-73-2)

Aquatic

Acute

EC50 Crustacea

Ceriodaphnia dubia

40.4 mg/l, 48 Hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

No data available.

Mobility in soil

Some components from a leaking battery may be mobile.

Other adverse effects

None known.

13. Disposal considerations

Disposal methods

Recycle the batteries, as the primary disposal method. Collect and reclaim or dispose in sealed

containers at licensed waste disposal site.

Residual waste

Dispose of in accordance with local regulations. This product and its container must be disposed

of in a safe manner.

Contaminated packaging

If contaminated by a leaking or damaged battery, empty containers should be taken to an

approved waste handling site for recycling or disposal.

14. Transport information

ADG

Not regulated as dangerous goods.

RID

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Nickel Metal Hydride (NiMH) Batteries 7/8

Version #: 02 Revision date: -Issue date: 31-January-2022 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Safety, health and environmental regulations

National regulations

This Safety Data Sheet was prepared in accordance with Australia Model Code of Practice for the preparation of Safety Data Sheets for Hazardous Chemicals (23/12/2011).

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP): This product is listed in Appendix A (General Exemptions) and hence the Standard does not apply to the substances in the product.

Australia National Pollutant Inventory (NPI): Threshold quantity

Cobalt (CAS 7440-48-4) 10 TONNES/YR Threshold Category: 1
Nickel (CAS 7440-02-0) 10 TONNES/YR Threshold Category: 1
Nickel hydroxide (CAS 12054-48-7) 10 TONNES/YR Threshold Category: 1

High Volume Industrial Chemicals (HVIC)

Nickel (CAS 7440-02-0) 1000 - 9999 TONNES See the regulation for additional

information.

Potassium hydroxide (CAS 1310-58-3) 1000 - 9999 TONNES See the regulation for additional

information.

Sodium hydroxide (CAS 1310-73-2) > 1000000 TONNES See the regulation for additional information.

Importation of Ozone Deleting Substances (Customs(Prohibited imports) Regulations 1956, Schedule 10)

Not listed

National Pollutant Inventory (NPI) substance reporting list

Nickel (CAS 7440-02-0) 2000 TONNES/YR Threshold Category: 2B Nickel hydroxide (CAS 12054-48-7) 2000 TONNES/YR Threshold Category: 2B

Prohibited Carcinogenic Substances

Not regulated.

Prohibited Substances (National Model Regulation for the control of Workplace Hazardous Substances, Schedule 2 NOHSC:1005 (1994) as amended)

Not listed.

Resricted Importation of Organochlorine Chemicals (Customs(Prohibited Imports) Regulations 1956, Schedule 9)

Not listed.

Restricted Carcinogenic Substances

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No

Country(s) or region Inventory name On inventory (yes/no)* Japan Inventory of Existing and New Chemical Substances (ENCS) Korea Existing Chemicals List (ECL) No

New Zealand New Zealand Inventory Yes No

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes *A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 31-January-2022

Revision date

Key abbreviations or acronyms used

ADG: Australian Dangerous Goods.

ACGIH: American Conference of Governmental Industrial Hygienists.

CAS: Chemical Abstracts Service.

IARC: International Agency for Research on Cancer. IATA: International Air Transport Association.

IBC: Intermediate Bulk Container.

IMDG: International Maritime Dangerous Goods.

MARPOL: International Convention for the Prevention of Pollution from Ships.

OEL: Occupational Exposure Limit.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short-Term Exposure Limit. TWA: Time Weighted Average.

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices References

IARC Monographs. Overall Evaluation of Carcinogenicity

ECHA registered substances database

Safe Work Australia Hazardous Substances Information System (HSIS)

Disclaimer Motorola Solutions, Inc. cannot anticipate all conditions under which this information and its

> product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

Nickel Metal Hydride (NiMH) Batteries